

IP Link® Device Interface Ethernet Communication Sheet

Revision: 3/27/2012

This document provides additional assistance with wiring your Extron IP Link enabled product to your device. Different components may require a different wiring scheme than those listed below.

For complete operating instructions, refer to the user's manual for the specific Extron IP Link enabled product or the controlled device manufacturer supplied documentation.

Device Specifications:

Device Type: Display
Manufacturer: Samsung
Firmware Version: N/A
Model(s): LN40D610M4F, LN46D610M4F

Minimum Software and Firmware Requirements:

IP Link Compiler	IP Link Firmware	GC Version
1.5.1	1.15	3.3.1

Version History:

Driver Version	Date	Notes
1	3/13/2012	Initial version.

Driver Notes:

IP Link® Device Interface Ethernet Communication Sheet

Revision: 3/27/2012

Control Commands & States:

Aspect Ratio	16:9	Zoom 1	Zoom 2
	Wide	4:3	Just Scan
	Smart View 1	Smart View 2	
Channel	Up	Down	
Input	TV	PC	HDMI1
	HDMI2	HDMI3	HDMI4
	Component 1	Component 2	Composite 1
	Composite 2		
Mute	Toggle		
Power Control	On	Off	
Volume (Discrete)	0 to 100 in steps of 1		
Volume (Step)	Up	Down	

Status Available:

N/A

IP Link® Device Interface Ethernet Communication Sheet

Revision: 3/27/2012

Network communication:

When configuring the Ethernet driver, be sure device settings match that of the GC configuration.

Port Type:	Ethernet
Logon Credentials Supported:	Undetermined
Default Port:	1515
Multi-Connection Capable:	Undetermined
Port Changeable:	Undetermined

Ethernet Driver Configuration Description:

Please refer to user manual for settings and changes to the network communication parameters.

Notes for the Device: